

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼

[Web History](#) | [Search settings](#) | [Sign in](#)


About 3,250,000 results (0.26 seconds)

[Advanced search](#)**Everything**

More

[Show search tools](#)**[HTTP/1.1: Header Field Definitions](#)**

part of Hypertext Transfer Protocol -- HTTP/1.1 If the request would, without the **If-Match** header field, result in anything ... to use the exact date **string** received in a previous Last-Modified header field whenever possible. ...

www.w3.org/Protocols/rfc2616/rfc2616-sec14.html - Cached - Similar
[HTTP/1.1: Protocol Parameters](#)

HTTP/1.1 uses transfer-coding values in the TE header field (section 14.39) and HTTP/1.1 uses entity tags in the ETag (section 14.19), **If-Match** (section ... An entity tag consists of an opaque quoted **string**, possibly prefixed by a ...

www.w3.org/Protocols/rfc2616-sec3.html - 16 hours ago - Cached - Similar

[Show more results from www.w3.org](#)
[DisplayFilters - The Wireshark Wiki](#)

Oct 20, 2008 ... The master list of display filter **protocol** fields can be found in the ... **Match** packets where SIP To-header contains the **string** "a1762" ...

wiki.wireshark.org/DisplayFilters - Cached - Similar
[Uses of Class org.apache.abdera.protocol.client.RequestOptions ...](#)

Methods in org.apache.abdera.protocol.client that return RequestOptions ... setIfMatch (String entity_tag) Sets the value of the HTTP If-Match header ...

abdera.apache.org/docs/api/.../protocol/.../RequestOptions.html - Cached - Similar
[RequestOptions \(Abdera Bundle Jar 0.4.0-incubating API\)](#)

Fields inherited from class org.apache.abdera.protocol.util. ... Create the RequestOptions object with the specified If-None-Match header value public RequestOptions setEncodedHeader(String header, String charset, String value) ...

abdera.apache.org/docs/api/.../protocol/.../RequestOptions.html - Cached - Similar
[Network-Based Application Recognition, Cisco IOS Release 12.2\(18\) ...](#)

no **match** protocol http [url uri-string] host hostname-string | mime MIME-type | c-header-field c-header-field-string | s-header-field s-header-field-string ...

https://www.cisco.com/.../products_feature_guida09186a0f80906451.html - Cached
[RFC 2616 - Hypertext Transfer Protocol -- HTTP/1.1](#)

HTTP allows an open-ended set of methods and **headers** that indicate the ... consisting of a structured sequence of octets **matching** the syntax Thus 2DIGIT is a 2-digit number, and 3ALPHA is a **string** of three alphabetic characters. ...

tools.ietf.org/html/rfc2616 - Cached - Similar
[download - Use of Entity Tags in XMPP Extensions](#)

Note: The ETag and If-None-Match headers SHOULD be used only in &IQ; ... some-new-opaque-string The payloads exchanged in the &xep0016; **protocol** can also be ...

xmpp.org/extensions/xep-0150.xml - Cached
[FREE STRING MATCH ENCODING AND PREVIEW - Patent application ...](#)

The user can select **protocol**, device address and free **string match** ... case" or "match case" or "start search for data at beginning of **protocol header**", ...

www.inq.org/patents/app/20090187588 - Cached
[Protocol Basics - Google Data Protocol - Google Code](#)

To do a full-text search for a particular **string**, when using a service that ... **If-Match**: *. The following example deletes an entry (if **headers** are set ...

code.google.com/apis/gdata/docs/2.0/basics.html - Cached - Similar

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)
[Next](#)

string exclusive OR match header Search

[Search within results](#)

[Search help](#)

[Give us feedback](#)

[Google Home](#)

[Advertising Programs](#)

[Business Solutions](#)

[Privacy](#)

[About Google](#)